

ac products, inc.

172 E. La Jolla Street, Placentia, CA 92870 ! (714) 630-7311 ! FAX (714) 666-8309

AC-807 REPAIRCOAT

PRODUCT DESCRIPTION

AC-807 Repaircoat is a one part, fast drying "liquid tape" that may be used to protect damaged areas in chemical milling maskants and stop-off coatings.

PRODUCT PERFORMANCE

AC-807 Repaircoat has been successfully used to repair pinholes, bubbles, and other damaged areas. Similar to AC-802 Topcoat, AC-807 Repaircoat provides excellent chemical resistance to hot corrosive solutions.

PRODUCT CHARACTERISTICS - AS SHIPPED

APPEARANCE	Red Viscous liquid
SOLIDS CONTENT (% BY WEIGHT)	23.0 ± 1.0
POUNDS PER GALLON	7.4 ± 0.2
FLASH POINT (T.O.C.)	45°F.
SHELF LIFE (AMBIENT TEMPERATURES).....	2 years
SOLVENT SYSTEM.....	Toluene

PRODUCT PRECAUTIONS

DANGER! FLAMMABLE. CONTAINS TOLUENE. VAPOR HARMFUL IF INHALED. KEEP OUT OF REACH OF CHILDREN. Avoid breathing vapor. Use with adequate ventilation. Keep away from heat, sparks, hot glowing surfaces, and open flame. Keep container closed when not in use. Avoid prolonged or repeated contact with skin. **DO NOT TAKE INTERNALLY.** Consult **MATERIAL SAFETY DATA SHEET** for handling and safety information.

PRODUCT PACKAGING

AC-807 Repaircoat is furnished in 5 gallon pour spout pails and 55 gallon steel drums.

PRODUCT USE INSTRUCTIONS

MIXING AND THINNING - Use as received. Mixing is not required. Should the material thicken during use due to evaporation, thin with toluene.

APPLICATION - Brush or dab AC-807 Repaircoat over the flaw to be repaired. When repairing a large bubble, break the skin and fill the void with Repaircoat.

CURE CYCLE - Repaircoat should dry to the touch in 5 to 10 minutes. Allow to air cure 1 to 2 hours before processing. Do not tightly stack parts immediately after applying. Allow an air space between the parts so that the Repaircoat may dry.

Seller makes no warranty of any kind, express or implied, as to the merchantability, fitness for any particular purpose, or any other matter with respect to this product. Since conditions of use are beyond seller's control, buyer assumes all risk of use of this product. Under no circumstances will seller be liable for consequential or incidental damages arising out of the use of this product. Seller's sole obligation shall be to replace the product if found to be defective. It is the user's responsibility to determine the suitability for use of this product under the conditions present at the time of application. M.S.D.S. available upon request.